2/ρκΤS

5

Method for adapting WAP-based transmissions

Description

The invention relates to a method for adapting WAP-
based transmissions. In particular, the invention
relates to the control of the flow of data in WAP-based
methods. In this context, the quality and flow are
predicted so as then to optimize the information
interchange through parameterization.

Field of the invention:

WAP is a protocol stack which is optimized for mobile
communication. This stack is used in most GSM or GPRS
applications of mobile terminals today; there is also
future provision for the stack to be used for UMTS
applications, and application in other environments
would also be conceivable. This is true at least for
Europe. WAP is not just a protocol, but rather
comprises all layers, from the application layer
through to layer 2. The WAP stack thus has five layers,
with all protocols having been specified by a forum.
The protocol is designed specifically for transmitting
data between mobile terminals and the mobile network.
There are thus different standards, WAP 1.0 and
WAP 2.0. It is now possible to use IETF protocols for
transmission and for session control. A WAP connection
exists between a client and a gateway, which is

connected to other services such as the Internet but
also to other services.

Hence, there is WAE (Wireless Application Environment),
5   which allows interactions between WAP/WEB applications
and wireless appliances which comprise a WAP browser.

There is also the WSP (Wireless Session Protocol),
which implements a functionality similar to HTTP and
10   provides new features, such as a very lengthy session,
and implements suspend and resume functionality. It is
also responsible for sending and getting information.
Suspend and resume can also be used to maintain a
connection or to interrupt it briefly, depending on
15   what the situation requires. This has the advantage
that the data which have already been sent do not need
to be sent again.

A further protocol is the WTP (Wireless Transaction
20   Protocol). This is a very simple transaction-oriented
protocol which can be used for implementing clients
(mobile terminals) and which operates efficiently over
wireless packet-oriented networks. This protocol is
responsible for transaction management, retransmission,
25   the removal of duplicates, control operations, packet
connections and disconnections, packet segmentation and
reassembly. The functionalities are comparable with
TCP. However, it is geared to connections which have
higher rates of error. There is thus no TTL (Time To
30   Live). There are different transaction classes,
retransmissions for confirmation and selective
retransmissions, selective confirmation operations and
asynchronous transactions, flexible confirmations
(HOLD) and moving transaction windows. These are just a
35   few features of this protocol.

Prior art:

[31] discloses a method which determines or predicts
the quality of the connection, particularly of the
uplink. This method is not tuned specifically to the
present protocol, however.

It is an object of the invention to influence and
improve the reliable protocol WAP to such an extent
that retransmissions are reduced and as a result a
higher. throughput is achieved. In this context, it is
necessary to take account of the quality of the
connection and cell change.

This object is achieved by the inventions having the
features of the independent claims. Advantageous
developments of the inventions are characterized in the
subclaims.

Seen abstractly, they involve a method which makes
decisions on the basis of calculations which determine
the future quality of the connection and also future
cell changes and implements them on the different
layers of the WAP protocol.

In this context, first of all short-term predictions
are made which decide about basic decisions such as
design of a connection or transmission and reception of
data.

Shorter-term predictions are used to alter a few
parameters which are associated with the transmission
of packets.

In particular, they involve a method for determining
parameters for WAP-based transmissions, where short-
term and long-term predictions are taken as a basis for.
making decisions about the type of transmission. For
long-term predictions about the possibility of setting

up a connection or the quality of a connection, decisions in the form of send or request data or suspend and resume the connection are made.

5   For decisions about sending and receiving (SEND and GET), basic decisions are made regarding whether data need to be received or need to be sent. Normally, such a starting point is flexible.

10 The commands SUSPEND and RESUME suspend a connection or resume it. Corresponding commands are known from the FTP protocol, for example. Should the short-term predictions, for example, predict an enormous degree of impairment and the long-term statements likewise, the

15 connection can be suspended. Should there be an improvement in the short-term and long-term predictions, the connection is restarted.

For short-term predictions regarding an existing

20 connection, a decision in the form of the number of asynchronous transactions or of the delay of a transmission or of a retransmission or alteration in the burst mode or of the adaptation of the packet size is made.

25

Should the quality fall below a particular value in future, for example, it is possible to delay the transmission of a packet. In particular, it can be delayed when a confirmation for the packet does not

30 need to be sent and has not arrived in an appropriate period of time. Particularly in the case of retransmissions, it is advantageous to determine an interval using a counter. Hence, WAP involves determining an interval using a counter which is

35 counted down. Should a retransmission be necessary, the counter or the interval is increased and counted down again. Depending on the quality, the interval can be increased or reduced. Should a very high quality be predicted, it is advantageous to send packets again

more quickly. If there is a shortfall below a
particular quality, a longer interval should be chosen.

It is thus possible to alter the number of parallel
5   transactions as a function of the quality of the
connection. Although a large number of transactions
with small packets increases the overhead of control
information over useful data, the error rate per packet
decreases. In addition, it may be necessary to increase
10 the number of simultaneous asynchronous transactions
for a few applications which run in parallel on the
terminal.

When adapting the burst rate, a large number of packets
15 are sent which are confirmed by a message from the
receiver. In this context, not every single packet is
confirmed, but just one sequence. Should there be
packets missing, the number of missing packets is
communicated. Should a connection have a high quality,
20 the burst rate can be increased. If packet loss can be
ruled out on the basis of the prediction, then the next
packet group (the next burst) is transmitted in
enforced fashion in order to avoid unnecessary waiting
times and to increase the data throughput. Should
25 packet loss be predicted, this response is reset again
and the next burst is transmitted in normal mode.

It is also possible to influence the packet size. If
there is just one packet then there is a higher
30 probability of errors arising. This probability can
thus be increased only if a high level of quality is
present or to be expected. In addition, when a cell
change is predicted, the packet length is chosen such
that the transmission of the packet can be concluded in
35 full in the old cell. The next packet's transaction
then involves waiting until the cell change has taken
place.

A cell change can be predicted whenever the signal strength in one cell decreases and the signal strengths in other surrounding cells increase. A prediction can therefore be made on the basis of the profile of the

5   signal strengths.

The method for predicting the quality preferably uses a multidimensional stochastic algorithm which, in particular, uses covariance matrices, neural networks,

10   genetic algorithms and/or simulated annealing. In this context, time-dependent statements about the quality or imminent cell change are calculated.

In the case of GSM/GPRS, preferably the received signal

15   code power (RSCP), the position, the direction, the level, the speed, the received signal strength indicator (RSSI), the block size, the codec, the header compression method, SNR, the volume of traffic, the transmission delay, the block error rate, the bit error

20   rate or carrier to interference ratio (C/I), power control commands are included in the calculation, with the outputs being determined therefrom. It is pointed out that these influencing variables cannot claim to be complete. It is likewise conceivable to use control

25   codes to carry out weighting operations which are included in the algorithm. It is also possible to have the quality of the uplinks and downlinks included in a particular ratio. In the case of UMTS, analog variables are used for calculation.

30

A further part of the present invention is a mobile terminal in the form of a PDA or of a GSM/GPRS/UMTS mobile phone, with means and the setup thereof, which allow the execution of a method as claimed in the

35   method claims. Normally, these apparatuses have one or more microprocessors which are controlled by software. This software implements the process, particularly the method for predicting the quality, on the one hand, and secondly the method which is used to make adaptations

on the basis of the predictions. The software does not necessarily need to be implemented just on one microprocessor; it is also possible for it to be logically distributed over a plurality of
5   microprocessors, which may also be located in different appliances (e.g. mobile phone and PDA).

The invention is explained in more detail below using exemplary embodiments which are shown schematically in
10 the figures. Identical reference numerals in the individual figures denote the same elements in this case. Specifically:

Figure 1   shows the schematic structure of the WAP
15   stack in version 1.x;

Figure 2   shows the schematic structure of the WAP
            stack in version 2.x with an integrated 1.x
            stack;
20

Figure 3   shows a table containing parameters, which
            may be part of the WAP stack, and their
            property over the transmission.

25 The text below describes examples of short/long-term predictions.

In the first example, there is a prediction that the carrier to interference ratio (C/I) will be
30 significantly impaired in the time in which the next packets will probably be transmitted, and will subsequently be at a very low level again. In this case, parameters which are effective in the short term would be used (send packet with a delay, reduce size of
35 packet groups ...). In the converse case (all quite well in the short term, with a long-lasting high level of interference subsequently appearing), attempts are made in the short term to transmit as much as possible (large number of transactions, large packet groups) so

as then to use long-term parameters in timely fashion (e.g. "suspend" the connection using SUSPEND).

Another example of long/short term is that CIR is known
5   to be good at present, but other information (transmission power close to the maximum permissible power ...) can be used to infer that the terminal is at the edge of the cell and hence the quality of the connection will soon become very poor. In this case
10   too, attempts are made to transmit the data quickly.

There follows a packet group/number of asynchronous transmissions example (number of transactions and packet groups):
15

The number of packets which can be transmitted in optimum fashion at a particular time is constant and known (given by available bandwidth and connection quality). There is now a free choice as to how this
20   number will be split.

Case A: either fewer asynchronous transmits (transmissions) and therefore larger packet groups or

25   Case B: more asynchronous transmits and therefore smaller packet groups

If a large message is to be sent or a particular action has higher priorities, then case A is taken into
30   account. This connection requires the largest possible packet group to be formed.

If, by contrast, a plurality of data volumes having equal authority are to be transmitted, then attempts
35   are made to transmit all of them with the same authority in parallel, that is to say case B. The table in figure 3 first of all shows the parameters which can be changed by the method by controlling them directly. Other parameters are not changed or controlled

indirectly. It is also possible to see which layer of
the layer model has the commands associated with it. A
further column in the table shows what effect they have
and whether they can be influenced directly by the
present method. It is thus possible to see from the
fifth column what influence they have on the
transmission.

List of cited literature:

[1]   3GPP TS 02.60: "General   Packet   Radio   Service
(GPRS); Service description; Stage 1"
[2]   3GPP TS 03.64: "Overall   description   of   the   GPRS
radio interface; Stage 2"
[3]   3GPP TS 05.01: "Physical layer on the radio path"
[4]   3GPP TS 05.05: "Radio transmission and reception"
[5]   3GPP TS 05.08: "Digital   cellular   tele-
communications system (Phase 2+); Radio subsystem link
control"
[7]   3GPP TS 05.10: "Digital   cellular   tele-
communications system (Phase 2+); Radio   subsystem
synchronization"
[8] Wireless   Application   Protocol   Architecture
Specification WAP-210-WAPArch
[9]   Wireless   Application   Protocol   WAP-199-WTLS
Wireless Transport Layer Security Specification
[10] Wireless Application Protocol WAP-224-WTP
[11] WAP-230-WSP Wireless Application Protocol Wireless
Session Protocol Specification
[12] Wireless Application Protocol WAP-236-WAESpec
[13] Wireless Application Protocol WAP-259-WDP
[14] TS 25.331: "RRC Protocol Specification"
[15] TS 25.322: "Radio Link Control (RLC) Protocol
Specification"
[16] TS 25.321: "Medium Access Control (MAC) Protocol
Specification"
[17] TS 25.215: "Physical layer - Measurements (FDD)"
[18] TS 25.225: "Physical layer - Measurements (TDD)"
[19] TS 25.932: "Access Stratum Delay Budget"

[20] G. Golub, Ch. Van Loan: Matrix Computations, Johns
Hopkins University Press, third edition, 1966

[21] EP 1 059 792 A2: "Method and system for wireless
QoS agent for All-IP network", Nortel Networks,
13.12.2000

[22] Larimore, W.E.:   (2000),   "Identification   of Colinear and Cointegrated Multivariable Systems Using Canonical Variate Analysis", in Preprints of Symposium on System Identification 2000, held June 21-23, 2000, Santa Barbara, CA

[23] Golub, Gene H.   and   Charles   Van   Loan,   Matrix Computations, Third Edition, Johns Hopkins University Press, Baltimore, 1996

[24] Wallace E. Larimore,   Franklin T. Luk,   "System Identification and control using SVD's on Systolic Arrays", SPIE Vol. 880 High Speed Computing (1988) QA 76.54 #54, 1988

[25] JP 09219697;   US 5,491,837;   US 5,710,791; US 5,506,869; US 5,845,208; US 5,878,342; US 5,886,988; US 5,828,658; US 6,101,383; US 6,137,993; US 5,794,155; WO 9610301;   WO 9913660;   WO 9951052;   WO 0004739; WO 0025530;   WO 0056103;   WO 0033479;   WO 9411972; EP 0455614;

[26] "Genetic   Algorithms   for   Control   and   Signal Processing",   K.F. Man,   S. Kwong,   W.A. Halang, K.S. Tang, ISBN: 3540761012, Springer-Verlag New York, 1996

[27] "Genetic Algorithms in Optimization, Simulation & Modeling", J. Stender, E. Hillebrand, J. Kingdon, ISBN: 9051991800, Press, Incorporated, 1994

[28] Basis   for   predicting   the   UMTS   FDD   uplink quality_v2

[29] "Genetic   Algorithms   &   Simulated   Annealing", Lawrence Davis, ISBN: 0273087711, Pitman Publishing, 1987

[30] "Applied   Simulated   Annealing",   Rene V. Vidal, ISBN: 038756229X, Springer-Verlag, 1993

[31] "Simulated Annealing: Theory and Applications", P.J. Van Laarhoven, Emile H. Aarts, ISBN: 9027725136, Kluwer Academic Publishers, 1987